# | PATROL + SHIELD | SHIELD 2

# EAC

## LIFELINE ON SUPPORT FOR TRAPEZOIDAL METAL ROOFS WITH AND WITHOUT **INSULATION LAYER**









# **COMPLETE**

The package includes fasteners and cellular rubber seals, to ensure waterproofing.









#### **APPLICATION**

Used on all trapezoidal metal roofs with and without insulation layer with spacing between frets of up to 420 mm.







## USE

SHIELD for use as a start, end or corner lifeline; SHIELD 2 for use as a straight intermediate point.










Installation of a PATROL lifeline with SHIELD supports on a steel sandwich panel roof.




### ■ PATROL LIFELINE COMPONENTS



#### ■ TECHNICAL DATA\*

substructure	minimum thickness	fastening systems included		
Fe	0,5 mm	SHIELD: rivet		
Fe Fe	0,5 mm	6,3 x 20,2 mm with EPDM washer (x 32)		
AI	1 mm	SHIELD2: rivet 6,3 x 20,2 mm		
-M	1 mm	with EPDM washer (x 16)		

		with SPEAR	with SPEAREVO	NEW
minimum spacing	x <sub>min</sub> [m]	2	2	
maximum spacing	x <sub>max</sub> [m]	7,5	15	
maximum deflection	y <sub>max</sub> [m]	1,44	3,40	
users	n.	2	4	



<sup>\*</sup> The values indicated are the result of experimental tests carried out under the supervision of third parties in accordance with the standard referred to. For a calculation report with minimum distances according to the relevant standard requirements, the substructure must be checked by a qualified engineer before installation.

# ■ SHIELD | CODES AND DIMENSIONS



CODE	description	material	В	Н	L	pcs	
			[mm]	[mm]	[mm]		
SHIELD	lifeline support	AISI 304 stainless steel grade 1.4301	180-420	85	476	1	H

## ■ SHIELD 2 | CODES AND DIMENSIONS

CODE	description	material	В	Н	L	pcs	
			[mm]	[mm]	[mm]		
SHIELD2	intermediate lifeline support	AISI 304 stainless steel grade 1.4301	250 - 370	65	322	1	H

#### COMPLEMENTARY PRODUCTS

CODE	description	pcs
RIV6320	rivets 6,3 x 20,2 mm with EPDM washer	33